# ComfortBreeze<sup>™</sup> CB100 & CB100S

Fan Powered Evaporative Humidifier



## PRODUCT DATA SHEET



## **Overview:**

As warm air passes across the moist humidifier pad, water is evaporated into the air stream. This raises the relative humidity of the air and contributes to the overall indoor air quality. Controlled humidity helps alleviate respiratory ailments as well as protect home furnishings and woodwork from the damages associated with dry air. ComfortBreeze™ humidifiers consume very little electricity and are available with optional, patented<sup>1</sup> H<sub>2</sub>OSmart™ Technology to minimize water consumption and maximize output capacity. H<sub>2</sub>OSmart controls are equipped with fault annunciation and a service indicator to assist in troubleshooting any problems that may occur. Since the CB100 is powered by its own fan, it may be used on any type furnace system and its capacity, operation and performance won't suffer due to minimal air volumes present with variable speed furnace systems.

## **Features:**

- H<sub>2</sub>OSmart Technology controls self adjust to compensate for variations in temperature, airflow, and water pressure allowing the CB100S to provide maximum performance and water savings regardless of system conditions. H<sub>2</sub>OSmart equipped humidifiers have the highest peak capacity\* and are the only humidifiers available with a constant drain water ratio.
- Environmentally Friendly ComfortBreeze<sup>™</sup> humidifiers consume less than 100 watts of electricity and H<sub>2</sub>OSmart Technology translates into greater than 80% water savings versus conventional competing units.
- Versatile Installation Fan-powered models are compatible with any type furnace system: single stage, variable speed, or modulating.
- Push-To-Lock Fittings Water connections provide quick and easy installation and worry-free operation.
- Fault Annunciation The CB100S provides LED indication of fault codes and when evaporative pad replacement is necessary.
- Independent Operation The CB100S can be installed so that a "call for heat" is not required for the unit to deliver humidification. H<sub>2</sub>OSmart equipped models feature a relay that can power the HVAC blower.

## **Operational Benefits:**

- H<sub>2</sub>OSmart Technology maximizes humidification capacity while conserving water across all temperature conditions.
- Increasing a home's relative humidity can make it feel comfortable at a lower temperature. (68°F can feel equivalent to a dry 73°F)
- Lower thermostat settings can deliver substantial savings on monthly energy bills. Every degree of setback represents about a 3% savings on heating costs.
- Save on energy costs while improving comfort.
- No need to plumb to hot water lines as is recommended for other evaporative humidifiers to "help" improve their performance. Our patented H<sub>2</sub>OSmart technology automatically maximizes evaporative performance without the added cost of using hot water.

## Warranty:

#### 5-Year Limited Warranty

<sup>1</sup>Air System Components, Inc. "Air Humidification Systems." Patent 9,285,133. 15 March 2016.

UNITS NOT FOR COMMERCIAL USE



# ComfortBreeze<sup>™</sup> CB100 & CB100S Fan Powered Evaporative Humidifier

## **PRODUCT DATA SHEET**

## ComfortBreeze<sup>™</sup> CB100 and CB100S

Model	CB100S with H₂OSmart <sup>™</sup> Technology	CB100
Part No.	265713-001	265713-002
Type of Unit	Fan Powered Evaporative	Fan Powered Evaporative
Peak Capacity (GPD)*	18 Gallons per Day	18 Gallons per Day
Humidistat Type	Electronic	Mechanical
H₂OSmart™ Technology	Yes	No
Capacity Reduction	Yes	No
Water Supply	20-100 PSI	20-100 PSI
Voltage (Amps)	120VAC (0.8A)	120VAC (0.8A)
Unit Dimensions	14.58" W x 11.24" D x 18.12" H	14.58" W x 11.24" D x 18.12" H
Water Connection	1/4" OD Tubing	1/4" OD Tubing
<b>Overflow Connection</b>	1/2" ID Tubing	1/2" ID Tubing
Shipping Weight	17 Lbs.	17 Lbs.
<b>Operating Weight</b>	13 Lbs.	13 Lbs.


**Optimum Zone** 

50%


\* Peak capacity as tested at 140°F air temperature. Nominal capacity at 120°F is 18 GPD.

40%

Upflow Bottom Return



Horizontal Flow



Upflow Side Return

#### Indoor Air Quality Since 1947

10%

20%

30%

ASHRAE

**Optimum Humidity Zone:** 

Organisms Bacteria

Viruses

Fungi

Mites

Rate of Respiratory Infections

Allergic Rhinitis and Asthma Reactions

Chemical Interactions

Ozone Production

**Relative Humidity** 

ISO 9001:2015 Certified

**Industry Memberships:** 



## www.trioniaq.com

#### **Proudly Designed**, Engineered, and Manufactured in the USA.\*

60%

70%

80%

90%



\*Manufactured with domestic and foreign components.

#### To help serve you better, please contact us at:

Organisms

Bacteria

Viruses

Fungi

Mites

Rate of Respiratory Infections

Allergic Rhinitis and Asthma Reactions

Chemical Interactions

Ozone Production

Relative Humidity

800-884-0002 (tel) 800-458-2379 (fax)

#### **TRION**® 101 McNeill Road Sanford, NC 27330 www.trioniaq.com customerservice@trioniaq.com

TRION® is a registered trademark of Air System Components, Inc. Air System Components, Inc. is a subsidiary of Johnson Controls Inc. All product specifications reflect available information at the printing of this brochure. TRION® reserves the right to revise or modify products and/or specifications without notice. © 2018 TRION®

T-CB100-0518